

World Class
Solutions

19" RACK SERVER NEMA 4/12 - UL LISTED ENCLOSURES

Strong & Durable Steel
Wall/Pole Mount Kit
Climate Control Options



NEMACO™

19" RACKMOUNT APPLICATIONS:

NEMACO offers exceptional and rugged indoor & outdoor wall/pole mount server rack enclosures & cabinets with industry standard 19" EIA adjustable rack rails for electronic equipment modules. The wall / pole mount 19" rackmount enclosures and cabinets are designed for both indoor & outdoor all weather conditions including the desert sun, heavy rain and ice cold weather snow storms. The Nemaco 19" rack mount enclosures have been installed for commercial security systems, satellite telecom, SCADA control systems, electrical hydro power plants and data acquisition systems for many industries, commercial and military applications.

INDUSTRY STANDARDS:

- UL 50 and UL 50E; File Number E507642
- cUL listed per CSA C22.2 No. 94; File Number E507642
- CSA C22.2 No. 94.1-15 and 94.2-15
- NEMA/EEMAC: Types 4, 4X, and 12
- IEC 60529 Type IP66



STANDARD FEATURES:

- Easy access front and rear doors provide great quick rack server equipment repair & maintenance.
- 2-post rackrails are standard for front door enclosure.
- 4-post rackrails are standard for front and rear door enclosure.
- 19" rackrails are designed to be fully adjustable in sliding tracks given flexibility setup.
- 19" rackrails come standard with #10-32 tapped holes.
- 3PT latch padlock handles are easy for everyday use.
- All seams are fully welded and ground smooth.
- Ground studs come standard on enclosure's door and body providing proper bonding and grounding.
- White, 61 Gray, 70 Gray, and Black powdercoat colors are standard colors.
- Standard 1/2" thick (R3.2) Radiant Barrier Insulation provides good thermal protection.
- Folded "Z" offset wall mount brackets with mounting holes provide flexibility in installation.

ENCLOSURE SPECIFICATIONS:

- NEMA 4 Gasket Door Seal for Water Resistance
- NEMA 4 Rated Door Hardware & Latches
- Precision Fit Door for Gasket Seal & Easy Turn Latch
- Continuous Welded Enclosure Corner Seams
- 12 gauge steel used on 60" tall and above enclosures
- 14 gauge steel used on below 60" tall enclosures
- EIA Standard Rack rails made of coated 12 gauge steel
- #10-32 tapped holes on rack rails (powder coated)
- 1/4-20 ground studs on enclosure's door and body
- Foam-in-place gasket with 1.25" extra wide
- Heavy duty 3pt. latch padlock handle
- Heavy duty lifting pads welded top
- Wall "Z" brackets are standard on left and right door enclosures

ACCESSORIES and MODIFICATIONS:

- 1,000 to 20,000 BTUH air-conditioned units
- 92 to 350 CFM filter fans
- A/C service hatch door
- Top and side sunshield cover
- Removable lifting pads
- Removable door hinge
- Key lockable handle
- Heavy duty Stainless rackrails
- 3/8 Square mounting rack holes
- 3/4" thk. (R5) and 1" thk. (R6) Radiant Insulation
- Rack shelves, Drawers, and supports
- Rack hardware, high point screw and cage nuts
- 19" Rack copper busbar
- Vertical rack PDU
- Custom powder coat colors
- Clear window kit (Non-UL option)
- Access cover plate with holes and cutouts
- Quad outlet box with receptacles
- Door stopper, 135 degree opening
- Door tamper switch
- Print pocket
- External mounting brackets
- Floor kit to provide extra mounting spots

NEMA 4/12 - POWDER COATED SERVER NETWORK ENCLOSURES

Dust & Water
Resistant
Protection



POWDER COATED
STEEL NEMA 4
ENCLOSURES



STEEL ENCLOSURE STANDARD FEATURES:

- Heavy duty lifting pads
- NEMA 4 gasket door seal for water resistance
- NEMA 4 rated door latch padlock handle
- Continuous welded enclosure corner seams
- Continuous steel door hinge
- 19" EIA 12 ga. standard rack rails
- #10-32 tapped holes on rack rails (powder coated)
- 1/4-20 ground studs on enclosure's door and body
- Offset Wall "Z" mounting brackets (2" offset)

ACCESSORIES:

- A/C service hatch door
- Top and side sunshield cover
- SS Key lockable handle
- Heavy duty Stainless rackrails
- Door stopper, 135 degree opening
- Floor mounting legs

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	16D	N4-242416-W1DCS19	24	24	16	14.5	19" EIA	12 RU	Galv. Steel	14 ga.	ANSI 61	81
Front		N4-302416-W1DCS19	30	24	16	14.5	19" EIA	15 RU	Galv. Steel	14 ga.	ANSI 61	90.49
Front		N4-362416-W1DCS19	36	24	16	14.5	19" EIA	18 RU	Galv. Steel	14 ga.	ANSI 61	102.33
Front		N4-422416-W1DCS19	42	24	16	14.5	19" EIA	22 RU	Galv. Steel	14 ga.	ANSI 61	114.49
Front		N4-482416-W1DCS19	48	24	16	14.5	19" EIA	25 RU	Galv. Steel	14 ga.	ANSI 61	135.07
Front		N4-542416-W1DCS19	54	24	16	14.5	19" EIA	29 RU	Galv. Steel	14 ga.	ANSI 61	145.31
Front		N4-602416-W1DCS19	60	24	16	14.5	19" EIA	32 RU	Galv. Steel	14 ga.	ANSI 61	157.14
Front		N4-662416-W1DCS19	66	24	16	14.5	19" EIA	36 RU	Galv. Steel	12 ga.	ANSI 61	226.26
Front		N4-722416-W1DCS19	72	24	16	14.5	19" EIA	39 RU	Galv. Steel	12 ga.	ANSI 61	239.56
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	20D	N4-242420-W1DCS19	24	24	20	18.5	19" EIA	12 RU	Galv. Steel	14 ga.	ANSI 61	92.31
Front		N4-302420-W1DCS19	30	24	20	18.5	19" EIA	15 RU	Galv. Steel	14 ga.	ANSI 61	102.87
Front		N4-362420-W1DCS19	36	24	20	18.5	19" EIA	18 RU	Galv. Steel	14 ga.	ANSI 61	115.77
Front		N4-422420-W1DCS19	42	24	20	18.5	19" EIA	22 RU	Galv. Steel	14 ga.	ANSI 61	129.01
Front		N4-482420-W1DCS19	48	24	20	18.5	19" EIA	25 RU	Galv. Steel	14 ga.	ANSI 61	150.65
Front		N4-542420-W1DCS19	54	24	20	18.5	19" EIA	29 RU	Galv. Steel	14 ga.	ANSI 61	161.95
Front		N4-602420-W1DCS19	60	24	20	18.5	19" EIA	32 RU	Galv. Steel	14 ga.	ANSI 61	174.85
Front		N4-662420-W1DCS19	66	24	20	18.5	19" EIA	36 RU	Galv. Steel	12 ga.	ANSI 61	251.4
Front		N4-722420-W1DCS19	72	24	20	18.5	19" EIA	39 RU	Galv. Steel	12 ga.	ANSI 61	266.2
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	24D	N4-242424-W1DCS19	24	24	24	22.5	19" EIA	12 RU	Galv. Steel	14 ga.	ANSI 61	112.05
Front		N4-302424-W1DCS19	30	24	24	22.5	19" EIA	15 RU	Galv. Steel	14 ga.	ANSI 61	123.68
Front		N4-362424-W1DCS19	36	24	24	22.5	19" EIA	18 RU	Galv. Steel	14 ga.	ANSI 61	137.64
Front		N4-422424-W1DCS19	42	24	24	22.5	19" EIA	22 RU	Galv. Steel	14 ga.	ANSI 61	151.94
Front		N4-482424-W1DCS19	48	24	24	22.5	19" EIA	25 RU	Galv. Steel	14 ga.	ANSI 61	169.2
Front		N4-542424-W1DCS19	54	24	24	22.5	19" EIA	29 RU	Galv. Steel	14 ga.	ANSI 61	181.57
Front		N4-602424-W1DCS19	60	24	24	22.5	19" EIA	32 RU	Galv. Steel	14 ga.	ANSI 61	195.53
Front		N4-662424-W1DCS19	66	24	24	22.5	19" EIA	36 RU	Galv. Steel	12 ga.	ANSI 61	279.52
Front		N4-722424-W1DCS19	72	24	24	22.5	19" EIA	39 RU	Galv. Steel	12 ga.	ANSI 61	295.81
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	30D	N4-242430-W1DCS19	24	24	30	28.5	19" EIA	12 RU	Galv. Steel	14 ga.	ANSI 61	129.02
Front		N4-302430-W1DCS19	30	24	30	28.5	19" EIA	15 RU	Galv. Steel	14 ga.	ANSI 61	142.25
Front		N4-362430-W1DCS19	36	24	30	28.5	19" EIA	18 RU	Galv. Steel	14 ga.	ANSI 61	157.81
Front		N4-422430-W1DCS19	42	24	30	28.5	19" EIA	22 RU	Galv. Steel	14 ga.	ANSI 61	173.71
Front		N4-482430-W1DCS19	48	24	30	28.5	19" EIA	25 RU	Galv. Steel	14 ga.	ANSI 61	192.57
Front		N4-542430-W1DCS19	54	24	30	28.5	19" EIA	29 RU	Galv. Steel	14 ga.	ANSI 61	206.53
Front		N4-602430-W1DCS19	60	24	30	28.5	19" EIA	32 RU	Galv. Steel	14 ga.	ANSI 61	222.1
Front		N4-662430-W1DCS19	66	24	30	28.5	19" EIA	36 RU	Galv. Steel	12 ga.	ANSI 61	317.24
Front		N4-722430-W1DCS19	72	24	30	28.5	19" EIA	39 RU	Galv. Steel	12 ga.	ANSI 61	335.77

NEMA 4/12 - Powder Coated 19" Wall / Pole Mount Enclosures Weatherproof - 1 and 2 Door - 19" Rack Cabinet Design

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	24D	N4-242424-W2DCS19	24	24	24	21	19" EIA	12 RU	Galv. Steel	14 ga.	ANSI 61	116.04
Left/Right		N4-302424-W2DCS19	30	24	24	21	19" EIA	15 RU	Galv. Steel	14 ga.	ANSI 61	128.88
Left/Right		N4-362424-W2DCS19	36	24	24	21	19" EIA	18 RU	Galv. Steel	14 ga.	ANSI 61	144.05
Left/Right		N4-422424-W2DCS19	42	24	24	21	19" EIA	22 RU	Galv. Steel	14 ga.	ANSI 61	159.71
Left/Right		N4-482424-W2DCS19	48	24	24	21	19" EIA	25 RU	Galv. Steel	14 ga.	ANSI 61	186.92
Left/Right		N4-542424-W2DCS19	54	24	24	21	19" EIA	29 RU	Galv. Steel	14 ga.	ANSI 61	200.64
Left/Right		N4-602424-W2DCS19	60	24	24	21	19" EIA	32 RU	Galv. Steel	14 ga.	ANSI 61	215.82
Left/Right		N4-662424-W2DCS19	66	24	24	21	19" EIA	36 RU	Galv. Steel	12 ga.	ANSI 61	304.29
Left/Right		N4-722424-W2DCS19	72	24	24	21	19" EIA	39 RU	Galv. Steel	12 ga.	ANSI 61	322.01
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	30D	N4-242430-W2DCS19	24	24	30	27	19" EIA	12 RU	Galv. Steel	14 ga.	ANSI 61	133.01
Left/Right		N4-302430-W2DCS19	30	24	30	27	19" EIA	15 RU	Galv. Steel	14 ga.	ANSI 61	147.45
Left/Right		N4-362430-W2DCS19	36	24	30	27	19" EIA	18 RU	Galv. Steel	14 ga.	ANSI 61	164.22
Left/Right		N4-422430-W2DCS19	42	24	30	27	19" EIA	22 RU	Galv. Steel	14 ga.	ANSI 61	181.48
Left/Right		N4-482430-W2DCS19	48	24	30	27	19" EIA	25 RU	Galv. Steel	14 ga.	ANSI 61	211.93
Left/Right		N4-542430-W2DCS19	54	24	30	27	19" EIA	29 RU	Galv. Steel	14 ga.	ANSI 61	227.25
Left/Right		N4-602430-W2DCS19	60	24	30	27	19" EIA	32 RU	Galv. Steel	14 ga.	ANSI 61	244.03
Left/Right		N4-662430-W2DCS19	66	24	30	27	19" EIA	36 RU	Galv. Steel	12 ga.	ANSI 61	344.3
Left/Right		N4-722430-W2DCS19	72	24	30	27	19" EIA	39 RU	Galv. Steel	12 ga.	ANSI 61	364.26
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	36D	N4-242436-W2DCS19	24	24	36	33	19" EIA	12 RU	Galv. Steel	14 ga.	ANSI 61	158.7
Left/Right		N4-302436-W2DCS19	30	24	36	33	19" EIA	15 RU	Galv. Steel	14 ga.	ANSI 61	174.74
Left/Right		N4-362436-W2DCS19	36	24	36	33	19" EIA	18 RU	Galv. Steel	14 ga.	ANSI 61	193.12
Left/Right		N4-422436-W2DCS19	42	24	36	33	19" EIA	22 RU	Galv. Steel	14 ga.	ANSI 61	212.69
Left/Right		N4-482436-W2DCS19	48	24	36	33	19" EIA	25 RU	Galv. Steel	14 ga.	ANSI 61	236.93
Left/Right		N4-542436-W2DCS19	54	24	36	33	19" EIA	29 RU	Galv. Steel	14 ga.	ANSI 61	253.85
Left/Right		N4-602436-W2DCS19	60	24	36	33	19" EIA	32 RU	Galv. Steel	14 ga.	ANSI 61	272.22
Left/Right		N4-662436-W2DCS19	66	24	36	33	19" EIA	36 RU	Galv. Steel	12 ga.	ANSI 61	384.3
Left/Right		N4-722436-W2DCS19	72	24	36	33	19" EIA	39 RU	Galv. Steel	12 ga.	ANSI 61	406.5
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	42D	N4-242442-W2DCS19	24	24	42	39	19" EIA	12 RU	Galv. Steel	14 ga.	ANSI 61	177.33
Left/Right		N4-302442-W2DCS19	30	24	42	39	19" EIA	15 RU	Galv. Steel	14 ga.	ANSI 61	194.97
Left/Right		N4-362442-W2DCS19	36	24	42	39	19" EIA	18 RU	Galv. Steel	14 ga.	ANSI 61	214.94
Left/Right		N4-422442-W2DCS19	42	24	42	39	19" EIA	22 RU	Galv. Steel	14 ga.	ANSI 61	235.39
Left/Right		N4-482442-W2DCS19	48	24	42	39	19" EIA	25 RU	Galv. Steel	14 ga.	ANSI 61	261.95
Left/Right		N4-542442-W2DCS19	54	24	42	39	19" EIA	29 RU	Galv. Steel	14 ga.	ANSI 61	280.47
Left/Right		N4-602442-W2DCS19	60	24	42	39	19" EIA	32 RU	Galv. Steel	14 ga.	ANSI 61	300.45
Left/Right		N4-662442-W2DCS19	66	24	42	39	19" EIA	36 RU	Galv. Steel	12 ga.	ANSI 61	424.34
Left/Right		N4-722442-W2DCS19	72	24	42	39	19" EIA	39 RU	Galv. Steel	12 ga.	ANSI 61	448.78



**19" RACKMOUNT NETWORK CABINET WITH OF 39RU & AIR-CONDITIONED
POWDER COATED ENCLOSURE - NEMACO PART# N4-722442-W2DCS19**

NEMA 4/12 - POWDER COATED ALUMINUM SERVER NETWORK ENCLOSURES

Light Weight
Powder Coated
Aluminum
Server Rack
Cabinets



ALUMINUM ENCLOSURE STANDARD FEATURES:

- Heavy duty removable lifting pads (standard)
- NEMA 4 gasket door seal for water resistance
- NEMA 4 rated door latch padlock handle
- Continuous welded enclosure corner seams
- Continuous stainless steel door hinge
- 19" EIA 12 ga. standard rack rails
- #10-32 tapped holes on rack rails (powder coated)
- 1/4-20 ground studs on enclosure's door and body
- Wall "Z" mounting brackets

ACCESSORIES:

- A/C service hatch door
- Top and side sunshield cover
- SS Key lockable handle
- Heavy duty Stainless rackrails
- Door stopper, 135 degree opening
- Floor mounting legs

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	16D	N4-242416-W1DAL19	24	24	16	14.5	19" EIA	12 RU	Aluminum	0.09	White	39.85
Front		N4-302416-W1DAL19	30	24	16	14.5	19" EIA	15 RU	Aluminum	0.09	White	44.71
Front		N4-362416-W1DAL19	36	24	16	14.5	19" EIA	18 RU	Aluminum	0.09	White	49.92
Front		N4-422416-W1DAL19	42	24	16	14.5	19" EIA	22 RU	Aluminum	0.125	White	70.38
Front		N4-482416-W1DAL19	48	24	16	14.5	19" EIA	25 RU	Aluminum	0.125	White	83.82
Front		N4-542416-W1DAL19	54	24	16	14.5	19" EIA	29 RU	Aluminum	0.125	White	89.92
Front		N4-602416-W1DAL19	60	24	16	14.5	19" EIA	32 RU	Aluminum	0.125	White	96.83
Front		N4-662416-W1DAL19	66	24	16	14.5	19" EIA	36 RU	Aluminum	0.125	White	103.89
Front		N4-722416-W1DAL19	72	24	16	14.5	19" EIA	39 RU	Aluminum	0.125	White	109.64
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	20D	N4-242420-W1DAL19	24	24	20	18.5	19" EIA	12 RU	Aluminum	0.09	White	46.02
Front		N4-302420-W1DAL19	30	24	20	18.5	19" EIA	15 RU	Aluminum	0.09	White	51.3
Front		N4-362420-W1DAL19	36	24	20	18.5	19" EIA	18 RU	Aluminum	0.09	White	56.93
Front		N4-422420-W1DAL19	42	24	20	18.5	19" EIA	22 RU	Aluminum	0.125	White	79.6
Front		N4-482420-W1DAL19	48	24	20	18.5	19" EIA	25 RU	Aluminum	0.125	White	93.63
Front		N4-542420-W1DAL19	54	24	20	18.5	19" EIA	29 RU	Aluminum	0.125	White	100.32
Front		N4-602420-W1DAL19	60	24	20	18.5	19" EIA	32 RU	Aluminum	0.125	White	107.82
Front		N4-662420-W1DAL19	66	24	20	18.5	19" EIA	36 RU	Aluminum	0.125	White	115.46
Front		N4-722420-W1DAL19	72	24	20	18.5	19" EIA	39 RU	Aluminum	0.125	White	121.79
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	24D	N4-242424-W1DAL19	24	24	24	22.5	19" EIA	12 RU	Aluminum	0.09	White	55.96
Front		N4-302424-W1DAL19	30	24	24	22.5	19" EIA	15 RU	Aluminum	0.09	White	61.66
Front		N4-362424-W1DAL19	36	24	24	22.5	19" EIA	18 RU	Aluminum	0.09	White	67.71
Front		N4-422424-W1DAL19	42	24	24	22.5	19" EIA	22 RU	Aluminum	0.125	White	93.12
Front		N4-482424-W1DAL19	48	24	24	22.5	19" EIA	25 RU	Aluminum	0.125	White	104.5
Front		N4-542424-W1DAL19	54	24	24	22.5	19" EIA	29 RU	Aluminum	0.125	White	111.77
Front		N4-602424-W1DAL19	60	24	24	22.5	19" EIA	32 RU	Aluminum	0.125	White	119.85
Front		N4-662424-W1DAL19	66	24	24	22.5	19" EIA	36 RU	Aluminum	0.125	White	128.08
Front		N4-722424-W1DAL19	72	24	24	22.5	19" EIA	39 RU	Aluminum	0.125	White	135
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	30D	N4-242430-W1DAL19	24	24	30	28.5	19" EIA	12 RU	Aluminum	0.09	White	66.78
Front		N4-302430-W1DAL19	30	24	30	28.5	19" EIA	15 RU	Aluminum	0.09	White	71.54
Front		N4-362430-W1DAL19	36	24	30	28.5	19" EIA	18 RU	Aluminum	0.09	White	78.23
Front		N4-422430-W1DAL19	42	24	30	28.5	19" EIA	22 RU	Aluminum	0.125	White	106.96
Front		N4-482430-W1DAL19	48	24	30	28.5	19" EIA	25 RU	Aluminum	0.125	White	119.21
Front		N4-542430-W1DAL19	54	24	30	28.5	19" EIA	29 RU	Aluminum	0.125	White	127.36
Front		N4-602430-W1DAL19	60	24	30	28.5	19" EIA	32 RU	Aluminum	0.125	White	136.33
Front		N4-662430-W1DAL19	66	24	30	28.5	19" EIA	36 RU	Aluminum	0.125	White	145.43
Front		N4-722430-W1DAL19	72	24	30	28.5	19" EIA	39 RU	Aluminum	0.125	White	153.23

**NEMA 4/12 - Powder Coated 19" Wall / Pole Mount Enclosures
Weatherproof - 1 and 2 Door - 19" Rack Cabinet Design**

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	24D	N4-242424-W2DAL19	24	24	24	21	19" EIA	12 RU	Aluminum	0.09	White	61.85
Left/Right		N4-302424-W2DAL19	30	24	24	21	19" EIA	15 RU	Aluminum	0.09	White	68.51
Left/Right		N4-362424-W2DAL19	36	24	24	21	19" EIA	18 RU	Aluminum	0.09	White	75.57
Left/Right		N4-422424-W2DAL19	42	24	24	21	19" EIA	22 RU	Aluminum	0.125	White	102.32
Left/Right		N4-482424-W2DAL19	48	24	24	21	19" EIA	25 RU	Aluminum	0.125	White	121.32
Left/Right		N4-542424-W2DAL19	54	24	24	21	19" EIA	29 RU	Aluminum	0.125	White	129.83
Left/Right		N4-602424-W2DAL19	60	24	24	21	19" EIA	32 RU	Aluminum	0.125	White	139.01
Left/Right		N4-662424-W2DAL19	66	24	24	21	19" EIA	36 RU	Aluminum	0.125	White	148.47
Left/Right		N4-722424-W2DAL19	72	24	24	21	19" EIA	39 RU	Aluminum	0.125	White	156.49
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	30D	N4-242430-W2DAL19	24	24	30	27	19" EIA	12 RU	Aluminum	0.09	White	72.67
Left/Right		N4-302430-W2DAL19	30	24	30	27	19" EIA	15 RU	Aluminum	0.09	White	78.4
Left/Right		N4-362430-W2DAL19	36	24	30	27	19" EIA	18 RU	Aluminum	0.09	White	86.09
Left/Right		N4-422430-W2DAL19	42	24	30	27	19" EIA	22 RU	Aluminum	0.125	White	116.15
Left/Right		N4-482430-W2DAL19	48	24	30	27	19" EIA	25 RU	Aluminum	0.125	White	136.93
Left/Right		N4-542430-W2DAL19	54	24	30	27	19" EIA	29 RU	Aluminum	0.125	White	146.32
Left/Right		N4-602430-W2DAL19	60	24	30	27	19" EIA	32 RU	Aluminum	0.125	White	156.38
Left/Right		N4-662430-W2DAL19	66	24	30	27	19" EIA	36 RU	Aluminum	0.125	White	166.72
Left/Right		N4-722430-W2DAL19	72	24	30	27	19" EIA	39 RU	Aluminum	0.125	White	174.08
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	36D	N4-242436-W2DAL19	24	24	36	33	19" EIA	12 RU	Aluminum	0.09	White	85.46
Left/Right		N4-302436-W2DAL19	30	24	36	33	19" EIA	15 RU	Aluminum	0.09	White	91.91
Left/Right		N4-362436-W2DAL19	36	24	36	33	19" EIA	18 RU	Aluminum	0.09	White	100.24
Left/Right		N4-422436-W2DAL19	42	24	36	33	19" EIA	22 RU	Aluminum	0.125	White	135.01
Left/Right		N4-482436-W2DAL19	48	24	36	33	19" EIA	25 RU	Aluminum	0.125	White	152.54
Left/Right		N4-542436-W2DAL19	54	24	36	33	19" EIA	29 RU	Aluminum	0.125	White	162.8
Left/Right		N4-602436-W2DAL19	60	24	36	33	19" EIA	32 RU	Aluminum	0.125	White	173.74
Left/Right		N4-662436-W2DAL19	66	24	36	33	19" EIA	36 RU	Aluminum	0.125	White	184.96
Left/Right		N4-722436-W2DAL19	72	24	36	33	19" EIA	39 RU	Aluminum	0.125	White	194.73
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	42D	N4-242442-W2DAL19	24	24	42	39	19" EIA	12 RU	Aluminum	0.09	White	95.37
Left/Right		N4-302442-W2DAL19	30	24	42	39	19" EIA	15 RU	Aluminum	0.09	White	102.45
Left/Right		N4-362442-W2DAL19	36	24	42	39	19" EIA	18 RU	Aluminum	0.09	White	111.41
Left/Right		N4-422442-W2DAL19	42	24	42	39	19" EIA	22 RU	Aluminum	0.125	White	149.76
Left/Right		N4-482442-W2DAL19	48	24	42	39	19" EIA	25 RU	Aluminum	0.125	White	168.16
Left/Right		N4-542442-W2DAL19	54	24	42	39	19" EIA	29 RU	Aluminum	0.125	White	179.3
Left/Right		N4-602442-W2DAL19	60	24	42	39	19" EIA	32 RU	Aluminum	0.125	White	191.12
Left/Right		N4-662442-W2DAL19	66	24	42	39	19" EIA	36 RU	Aluminum	0.125	White	203.22
Left/Right		N4-722442-W2DAL19	72	24	42	39	19" EIA	39 RU	Aluminum	0.125	White	213.87



**EASY ACCESS - 2 DOOR DESIGN - FULL ACCESS FOR 19" RACK NETWORK EQUIPMENT
ALUMINUM ENCLOSURE - NEMACO PART# N4-542436-W2DAL19 WITH A/C OPTION**