

**World Class  
Solutions**

**19" RACK MOUNT  
NEMA 4X - UL LISTED  
NETWORK ENCLOSURES**

**304 & 316L Stainless Steel  
Pole / Wall Mount Kit  
Climate Control Options**



**ENCLOSURE APPLICATIONS:**

NEMACO offers exceptional and rugged stainless steel indoor & outdoor Network Server Rackmount Enclosures & Cabinets with industry standard 19" EIA adjustable rack rails for network server modules with space for uninterruptable power supplies (UPS) and power distribution units (PDU). Nemaco 19" rackmount enclosures and cabinets are designed for all weather conditions including the desert sun, cold wet rainy and freezing ice storms. The network server cabinets are used telecommunication, security, surveillance, radar systems, SCADA control systems, electronic power plants, and many other applications.

**INDUSTRY STANDARDS:**

- UL 50 and UL 50E; File Number E507642
- cUL listed per CSA C22.2 No. 94; File Number E507642
- CSA C22.2 No. 94.1-15 and 94.2-15
- NEMA/EEMAC: Types 4, 4X, and 12
- IEC 60529 Type IP66



**STANDARD FEATURES:**

- Easy access left and right doors provide great quick access for maintenance, replace, and repair of equipment.
- 2-post rackrails are standard for front door enclosure.
- 4-post rackrails are standard for left and right door enclosure.
- 19" rackrails are designed to be fully adjustable in sliding tracks given flexibility setup.
- 19" rackrails come standard with #10-32 tapped holes.
- 3PT latch SS padlock handles are easy for everyday use.
- All seams are fully welded and ground smooth.
- Ground studs come standard on enclosure's door and body providing proper bonding and grounding.
- White, 61 Gray, 70 Gray, and Black powdercoat colors are standard colors.
- Standard 1/2" thick (R3.2) Radiant Barrier Insulation provides good thermal protection.
- Folded "Z" offset wall mount brackets with mounting holes provide flexibility in installation.

**ENCLOSURE SPECIFICATIONS:**

- NEMA 4X Gasket Door Seal for Water Resistance
- NEMA 4X Rated Door Hardware & Latches
- Precision Fit Door for Gasket Seal & Easy Turn Latch
- Continuous Welded Enclosure Corner Seams
- 12 gauge steel used on 60" tall and above enclosures
- 14 gauge steel used on below 60" tall enclosures
- EIA Standard Rack rails made of coated 12 gauge steel
- #10-32 tapped holes on rack rails (powder coated)
- 1/4-20 ground studs on enclosure's door and body
- Foam-in-place gasket with 1.25" extra wide
- Heavy duty 3pt. latch padlock handle
- Heavy duty lifting pads welded top
- Wall tabs are standard on front door enclosures
- Wall "Z" brackets are standard on left and right door enclosures

**ACCESSORIES and MODIFICATIONS:**

- 1,000 to 20,000 BTUH SS air-conditioned units
- 92 to 350 CFM SS filter fans
- A/C service hatch door
- Top and side sunshield cover
- Removable lifting pads
- Removable door hinge
- SS Key lockable handle
- Heavy duty Stainless rackrails
- 3/8 Square mounting rack holes
- 3/4" thk. (R5) and 1" thk. (R6) Radiant Insulation
- Rack shelves, drawers, and supports
- Rack hardware, high point screw and cage nuts
- 19" Rack copper busbar
- Vertical rack PDU
- Custom powder coat colors
- Clear window kit (Non-UL option)
- Access cover plate with holes and cutouts
- Quad outlet box with receptacles
- Door stopper, 135 degree opening
- Door tamper switch (electric switch)
- Print pockets (large & small)
- Floor Kit Tabs (for exterior mounting tabs on base)

**NEMA 4X - 316L STAINLESS STEEL - NETWORK ENCLOSURES**

**WASHDOWN  
WEATHERPROOF  
PROTECTION**



**NEMA 4X  
STAINLESS  
STEEL**



**ENCLOSURE STANDARD FEATURES:**

- Heavy duty 316SS lifting pads
- NEMA 4X gasket door seal for water resistance
- NEMA 4X rated door latch padlock handle
- Continuous welded enclosure corner seams
- Continuous 316SS door hinge
- 19" EIA 12 ga. standard rack rails
- #10-32 tapped holes on rack rails (powder coated)
- 1/4-20 ground studs on enclosure's door and body
- Offset Wall "Z" mounting brackets (2" wall gap)

**ACCESSORIES:**

- A/C service hatch door
- Top and side sunshield cover
- SS Key lockable handle
- Heavy duty Stainless rackrails
- Door stopper, 135 degree opening
- External mounting brackets
- Floor mounting legs

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	16D	N4X242416-W1DS619	24	24	16	14.5	19" EIA	12 RU	316SS	14 ga.	#4 Grain	80.84
Front		N4X302416-W1DS619	30	24	16	14.5	19" EIA	15 RU	316SS	14 ga.	#4 Grain	92.21
Front		N4X362416-W1DS619	36	24	16	14.5	19" EIA	18 RU	316SS	14 ga.	#4 Grain	104.36
Front		N4X422416-W1DS619	42	24	16	14.5	19" EIA	22 RU	316SS	14 ga.	#4 Grain	116.85
Front		N4X482416-W1DS619	48	24	16	14.5	19" EIA	25 RU	316SS	14 ga.	#4 Grain	137.84
Front		N4X542416-W1DS619	54	24	16	14.5	19" EIA	29 RU	316SS	14 ga.	#4 Grain	148.36
Front		N4X602416-W1DS619	60	24	16	14.5	19" EIA	32 RU	316SS	14 ga.	#4 Grain	160.51
Front		N4X662416-W1DS619	66	24	16	14.5	19" EIA	36 RU	316SS	12 ga.	#4 Grain	230.97
Front		N4X722416-W1DS619	72	24	16	14.5	19" EIA	39 RU	316SS	12 ga.	#4 Grain	244.62
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	20D	N4X242420-W1DS619	24	24	20	18.5	19" EIA	12 RU	316SS	14 ga.	#4 Grain	92.29
Front		N4X302420-W1DS619	30	24	20	18.5	19" EIA	15 RU	316SS	14 ga.	#4 Grain	104.75
Front		N4X362420-W1DS619	36	24	20	18.5	19" EIA	18 RU	316SS	14 ga.	#4 Grain	117.98
Front		N4X422420-W1DS619	42	24	20	18.5	19" EIA	22 RU	316SS	14 ga.	#4 Grain	131.56
Front		N4X482420-W1DS619	48	24	20	18.5	19" EIA	25 RU	316SS	14 ga.	#4 Grain	153.63
Front		N4X542420-W1DS619	54	24	20	18.5	19" EIA	29 RU	316SS	14 ga.	#4 Grain	165.24
Front		N4X602420-W1DS619	60	24	20	18.5	19" EIA	32 RU	316SS	14 ga.	#4 Grain	178.47
Front		N4X662420-W1DS619	66	24	20	18.5	19" EIA	36 RU	316SS	12 ga.	#4 Grain	256.49
Front		N4X722420-W1DS619	72	24	20	18.5	19" EIA	39 RU	316SS	12 ga.	#4 Grain	271.65
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	24D	N4X242424-W1DS619	24	24	24	22.5	19" EIA	12 RU	316SS	14 ga.	#4 Grain	110.72
Front		N4X302424-W1DS619	30	24	24	22.5	19" EIA	15 RU	316SS	14 ga.	#4 Grain	124.26
Front		N4X362424-W1DS619	36	24	24	22.5	19" EIA	18 RU	316SS	14 ga.	#4 Grain	138.58
Front		N4X422424-W1DS619	42	24	24	22.5	19" EIA	22 RU	316SS	14 ga.	#4 Grain	153.24
Front		N4X482424-W1DS619	48	24	24	22.5	19" EIA	25 RU	316SS	14 ga.	#4 Grain	170.85
Front		N4X542424-W1DS619	54	24	24	22.5	19" EIA	29 RU	316SS	14 ga.	#4 Grain	183.54
Front		N4X602424-W1DS619	60	24	24	22.5	19" EIA	32 RU	316SS	14 ga.	#4 Grain	197.86
Front		N4X662424-W1DS619	66	24	24	22.5	19" EIA	36 RU	316SS	12 ga.	#4 Grain	283.44
Front		N4X722424-W1DS619	72	24	24	22.5	19" EIA	39 RU	316SS	12 ga.	#4 Grain	300.12
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	30D	N4X242430-W1DS619	24	24	30	28.5	19" EIA	12 RU	316SS	14 ga.	#4 Grain	127.9
Front		N4X302430-W1DS619	30	24	30	28.5	19" EIA	15 RU	316SS	14 ga.	#4 Grain	143.07
Front		N4X362430-W1DS619	36	24	30	28.5	19" EIA	18 RU	316SS	14 ga.	#4 Grain	159.01
Front		N4X422430-W1DS619	42	24	30	28.5	19" EIA	22 RU	316SS	14 ga.	#4 Grain	175.29
Front		N4X482430-W1DS619	48	24	30	28.5	19" EIA	25 RU	316SS	14 ga.	#4 Grain	194.53
Front		N4X542430-W1DS619	54	24	30	28.5	19" EIA	29 RU	316SS	14 ga.	#4 Grain	208.85
Front		N4X602430-W1DS619	60	24	30	28.5	19" EIA	32 RU	316SS	14 ga.	#4 Grain	224.79
Front		N4X662430-W1DS619	66	24	30	28.5	19" EIA	36 RU	316SS	12 ga.	#4 Grain	321.71
Front		N4X722430-W1DS619	72	24	30	28.5	19" EIA	39 RU	316SS	12 ga.	#4 Grain	340.67

Nemaco Technology, LLC. "Nemaco" is a trademark of Nemaco Technology, LLC. All Rights Reserved.

Specifications are subject to change without notice. Nemaco-N4X-19R-WM-1D-2D-Rev2024-04-20

**NEMA 4X - 19" Rackmount - Wall Mount Enclosure**  
**304 / 316L Stainless Steel - 1 or 2 Door Designs**

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	24D	N4X242424-W2DS619	24	24	24	21	19" EIA	12 RU	316SS	14 ga.	#4 Grain	116.69
Left/Right		N4X302424-W2DS619	30	24	24	21	19" EIA	15 RU	316SS	14 ga.	#4 Grain	131.59
Left/Right		N4X362424-W2DS619	36	24	24	21	19" EIA	18 RU	316SS	14 ga.	#4 Grain	147.26
Left/Right		N4X422424-W2DS619	42	24	24	21	19" EIA	22 RU	316SS	14 ga.	#4 Grain	163.41
Left/Right		N4X482424-W2DS619	48	24	24	21	19" EIA	25 RU	316SS	14 ga.	#4 Grain	191.21
Left/Right		N4X542424-W2DS619	54	24	24	21	19" EIA	29 RU	316SS	14 ga.	#4 Grain	205.4
Left/Right		N4X602424-W2DS619	60	24	24	21	19" EIA	32 RU	316SS	14 ga.	#4 Grain	221.08
Left/Right		N4X662424-W2DS619	66	24	24	21	19" EIA	36 RU	316SS	12 ga.	#4 Grain	311.32
Left/Right		N4X722424-W2DS619	72	24	24	21	19" EIA	39 RU	316SS	12 ga.	#4 Grain	329.59
Left/Right		N4X722424-W2DS619	72	24	24	21	19" EIA	39 RU	316SS	12 ga.	#4 Grain	329.59
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	30D	N4X242430-W2DS619	24	24	30	27	19" EIA	12 RU	316SS	14 ga.	#4 Grain	133.87
Left/Right		N4X302430-W2DS619	30	24	30	27	19" EIA	15 RU	316SS	14 ga.	#4 Grain	150.39
Left/Right		N4X362430-W2DS619	36	24	30	27	19" EIA	18 RU	316SS	14 ga.	#4 Grain	167.69
Left/Right		N4X422430-W2DS619	42	24	30	27	19" EIA	22 RU	316SS	14 ga.	#4 Grain	185.47
Left/Right		N4X482430-W2DS619	48	24	30	27	19" EIA	25 RU	316SS	14 ga.	#4 Grain	216.57
Left/Right		N4X542430-W2DS619	54	24	30	27	19" EIA	29 RU	316SS	14 ga.	#4 Grain	232.38
Left/Right		N4X602430-W2DS619	60	24	30	27	19" EIA	32 RU	316SS	14 ga.	#4 Grain	249.68
Left/Right		N4X662430-W2DS619	66	24	30	27	19" EIA	36 RU	316SS	12 ga.	#4 Grain	351.93
Left/Right		N4X722430-W2DS619	72	24	30	27	19" EIA	39 RU	316SS	12 ga.	#4 Grain	372.47
Left/Right		N4X722430-W2DS619	72	24	30	27	19" EIA	39 RU	316SS	12 ga.	#4 Grain	372.47
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	36D	N4X242436-W2DS619	24	24	36	33	19" EIA	12 RU	316SS	14 ga.	#4 Grain	159.92
Left/Right		N4X302436-W2DS619	30	24	36	33	19" EIA	15 RU	316SS	14 ga.	#4 Grain	178.07
Left/Right		N4X362436-W2DS619	36	24	36	33	19" EIA	18 RU	316SS	14 ga.	#4 Grain	196.99
Left/Right		N4X422436-W2DS619	42	24	36	33	19" EIA	22 RU	316SS	14 ga.	#4 Grain	216.4
Left/Right		N4X482436-W2DS619	48	24	36	33	19" EIA	25 RU	316SS	14 ga.	#4 Grain	241.91
Left/Right		N4X542436-W2DS619	54	24	36	33	19" EIA	29 RU	316SS	14 ga.	#4 Grain	259.35
Left/Right		N4X602436-W2DS619	60	24	36	33	19" EIA	32 RU	316SS	14 ga.	#4 Grain	278.27
Left/Right		N4X662436-W2DS619	66	24	36	33	19" EIA	36 RU	316SS	12 ga.	#4 Grain	392.52
Left/Right		N4X722436-W2DS619	72	24	36	33	19" EIA	39 RU	316SS	12 ga.	#4 Grain	415.33
Left/Right		N4X722436-W2DS619	72	24	36	33	19" EIA	39 RU	316SS	12 ga.	#4 Grain	415.33
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	42D	N4X242442-W2DS619	24	24	42	39	19" EIA	12 RU	316SS	14 ga.	#4 Grain	178.79
Left/Right		N4X302442-W2DS619	30	24	42	39	19" EIA	15 RU	316SS	14 ga.	#4 Grain	198.56
Left/Right		N4X362442-W2DS619	36	24	42	39	19" EIA	18 RU	316SS	14 ga.	#4 Grain	219.11
Left/Right		N4X422442-W2DS619	42	24	42	39	19" EIA	22 RU	316SS	14 ga.	#4 Grain	240.14
Left/Right		N4X482442-W2DS619	48	24	42	39	19" EIA	25 RU	316SS	14 ga.	#4 Grain	267.28
Left/Right		N4X542442-W2DS619	54	24	42	39	19" EIA	29 RU	316SS	14 ga.	#4 Grain	286.34
Left/Right		N4X602442-W2DS619	60	24	42	39	19" EIA	32 RU	316SS	14 ga.	#4 Grain	306.89
Left/Right		N4X662442-W2DS619	66	24	42	39	19" EIA	36 RU	316SS	12 ga.	#4 Grain	433.15
Left/Right		N4X722442-W2DS619	72	24	42	39	19" EIA	39 RU	316SS	12 ga.	#4 Grain	458.24
Left/Right		N4X722442-W2DS619	72	24	42	39	19" EIA	39 RU	316SS	12 ga.	#4 Grain	458.24



**FULL ACCESS - NETWORK SERVER ENCLOSURE - AIR CONDITIONER OPTION**  
**39U NEMA 4X 316SS ENCLOSURE - NEMACO PART# N4X722442-W2DS619**

**NEMA 4X - 304 STAINLESS STEEL - NETWORK ENCLOSURES**

**WASHDOWN  
WEATHERPROOF  
PROTECTION**



**304 STAINLESS  
STEEL NEMA 4X  
ENCLOSURES**



**ENCLOSURE STANDARD FEATURES:**

- Heavy duty 316SS lifting pads
- NEMA 4X gasket door seal for water resistance
- NEMA 4X rated door latch padlock handle
- Continuous welded enclosure corner seams
- Continuous 316SS door hinge
- 19" EIA 12 ga. standard rack rails
- #10-32 tapped holes on rack rails (powder coated)
- 1/4-20 ground studs on enclosure's door and body
- Wall "Z" mounting brackets

**ACCESSORIES:**

- A/C service hatch door
- Top and side sunshield cover
- SS Key lockable handle
- Heavy duty Stainless rackrails
- Door stopper, 135 degree opening
- External mounting brackets
- Floor mounting legs

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	16D	N4X242416-W1DS419	24	24	16	14.5	19" EIA	12 RU	304SS	14 ga.	#4 Grain	80.84
Front		N4X302416-W1DS419	30	24	16	14.5	19" EIA	15 RU	304SS	14 ga.	#4 Grain	92.21
Front		N4X362416-W1DS419	36	24	16	14.5	19" EIA	18 RU	304SS	14 ga.	#4 Grain	104.36
Front		N4X422416-W1DS419	42	24	16	14.5	19" EIA	22 RU	304SS	14 ga.	#4 Grain	116.85
Front		N4X482416-W1DS419	48	24	16	14.5	19" EIA	25 RU	304SS	14 ga.	#4 Grain	137.84
Front		N4X542416-W1DS419	54	24	16	14.5	19" EIA	29 RU	304SS	14 ga.	#4 Grain	148.36
Front		N4X602416-W1DS419	60	24	16	14.5	19" EIA	32 RU	304SS	14 ga.	#4 Grain	160.51
Front		N4X662416-W1DS419	66	24	16	14.5	19" EIA	36 RU	304SS	12 ga.	#4 Grain	230.97
Front		N4X722416-W1DS419	72	24	16	14.5	19" EIA	39 RU	304SS	12 ga.	#4 Grain	244.62
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	20D	N4X242420-W1DS419	24	24	20	18.5	19" EIA	12 RU	304SS	14 ga.	#4 Grain	92.29
Front		N4X302420-W1DS419	30	24	20	18.5	19" EIA	15 RU	304SS	14 ga.	#4 Grain	104.75
Front		N4X362420-W1DS419	36	24	20	18.5	19" EIA	18 RU	304SS	14 ga.	#4 Grain	117.98
Front		N4X422420-W1DS419	42	24	20	18.5	19" EIA	22 RU	304SS	14 ga.	#4 Grain	131.56
Front		N4X482420-W1DS419	48	24	20	18.5	19" EIA	25 RU	304SS	14 ga.	#4 Grain	153.63
Front		N4X542420-W1DS419	54	24	20	18.5	19" EIA	29 RU	304SS	14 ga.	#4 Grain	165.24
Front		N4X602420-W1DS419	60	24	20	18.5	19" EIA	32 RU	304SS	14 ga.	#4 Grain	178.47
Front		N4X662420-W1DS419	66	24	20	18.5	19" EIA	36 RU	304SS	12 ga.	#4 Grain	256.49
Front		N4X722420-W1DS419	72	24	20	18.5	19" EIA	39 RU	304SS	12 ga.	#4 Grain	271.65
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	24D	N4X242424-W1DS419	24	24	24	22.5	19" EIA	12 RU	304SS	14 ga.	#4 Grain	110.72
Front		N4X302424-W1DS419	30	24	24	22.5	19" EIA	15 RU	304SS	14 ga.	#4 Grain	124.26
Front		N4X362424-W1DS419	36	24	24	22.5	19" EIA	18 RU	304SS	14 ga.	#4 Grain	138.58
Front		N4X422424-W1DS419	42	24	24	22.5	19" EIA	22 RU	304SS	14 ga.	#4 Grain	153.24
Front		N4X482424-W1DS419	48	24	24	22.5	19" EIA	25 RU	304SS	14 ga.	#4 Grain	170.85
Front		N4X542424-W1DS419	54	24	24	22.5	19" EIA	29 RU	304SS	14 ga.	#4 Grain	183.54
Front		N4X602424-W1DS419	60	24	24	22.5	19" EIA	32 RU	304SS	14 ga.	#4 Grain	197.86
Front		N4X662424-W1DS419	66	24	24	22.5	19" EIA	36 RU	304SS	12 ga.	#4 Grain	283.44
Front		N4X722424-W1DS419	72	24	24	22.5	19" EIA	39 RU	304SS	12 ga.	#4 Grain	300.12
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	30D	N4X242430-W1DS419	24	24	30	28.5	19" EIA	12 RU	304SS	14 ga.	#4 Grain	127.9
Front		N4X302430-W1DS419	30	24	30	28.5	19" EIA	15 RU	304SS	14 ga.	#4 Grain	143.07
Front		N4X362430-W1DS419	36	24	30	28.5	19" EIA	18 RU	304SS	14 ga.	#4 Grain	159.01
Front		N4X422430-W1DS419	42	24	30	28.5	19" EIA	22 RU	304SS	14 ga.	#4 Grain	175.29
Front		N4X482430-W1DS419	48	24	30	28.5	19" EIA	25 RU	304SS	14 ga.	#4 Grain	194.53
Front		N4X542430-W1DS419	54	24	30	28.5	19" EIA	29 RU	304SS	14 ga.	#4 Grain	208.85
Front		N4X602430-W1DS419	60	24	30	28.5	19" EIA	32 RU	304SS	14 ga.	#4 Grain	224.79
Front		N4X662430-W1DS419	66	24	30	28.5	19" EIA	36 RU	304SS	12 ga.	#4 Grain	321.71
Front		N4X722430-W1DS419	72	24	30	28.5	19" EIA	39 RU	304SS	12 ga.	#4 Grain	340.67

Nemaco Technology, LLC. "Nemaco" is a trademark of Nemaco Technology, LLC. All Rights Reserved.

Specifications are subject to change without notice. Nemaco-N4X-19R-WM-1D-2D-Rev2024-04-20

**NEMA 4X - 19" Rackmount - Wall Mount Enclosure**  
**304 / 316L Stainless Steel - 1 or 2 Door Designs**

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	24D	N4X242424-W2DS419	24	24	24	21	19" EIA	12 RU	304SS	14 ga.	#4 Grain	116.69
Left/Right		N4X302424-W2DS419	30	24	24	21	19" EIA	15 RU	304SS	14 ga.	#4 Grain	131.59
Left/Right		N4X362424-W2DS419	36	24	24	21	19" EIA	18 RU	304SS	14 ga.	#4 Grain	147.26
Left/Right		N4X422424-W2DS419	42	24	24	21	19" EIA	22 RU	304SS	14 ga.	#4 Grain	163.41
Left/Right		N4X482424-W2DS419	48	24	24	21	19" EIA	25 RU	304SS	14 ga.	#4 Grain	191.21
Left/Right		N4X542424-W2DS419	54	24	24	21	19" EIA	29 RU	304SS	14 ga.	#4 Grain	205.4
Left/Right		N4X602424-W2DS419	60	24	24	21	19" EIA	32 RU	304SS	14 ga.	#4 Grain	221.08
Left/Right		N4X662424-W2DS419	66	24	24	21	19" EIA	36 RU	304SS	12 ga.	#4 Grain	311.32
Left/Right		N4X722424-W2DS419	72	24	24	21	19" EIA	39 RU	304SS	12 ga.	#4 Grain	329.59
Left/Right		N4X722424-W2DS419	72	24	24	21	19" EIA	39 RU	304SS	12 ga.	#4 Grain	329.59
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	30D	N4X242430-W2DS419	24	24	30	27	19" EIA	12 RU	304SS	14 ga.	#4 Grain	133.87
Left/Right		N4X302430-W2DS419	30	24	30	27	19" EIA	15 RU	304SS	14 ga.	#4 Grain	150.39
Left/Right		N4X362430-W2DS419	36	24	30	27	19" EIA	18 RU	304SS	14 ga.	#4 Grain	167.69
Left/Right		N4X422430-W2DS419	42	24	30	27	19" EIA	22 RU	304SS	14 ga.	#4 Grain	185.47
Left/Right		N4X482430-W2DS419	48	24	30	27	19" EIA	25 RU	304SS	14 ga.	#4 Grain	216.57
Left/Right		N4X542430-W2DS419	54	24	30	27	19" EIA	29 RU	304SS	14 ga.	#4 Grain	232.38
Left/Right		N4X602430-W2DS419	60	24	30	27	19" EIA	32 RU	304SS	14 ga.	#4 Grain	249.68
Left/Right		N4X662430-W2DS419	66	24	30	27	19" EIA	36 RU	304SS	12 ga.	#4 Grain	351.93
Left/Right		N4X722430-W2DS419	72	24	30	27	19" EIA	39 RU	304SS	12 ga.	#4 Grain	372.47
Left/Right		N4X722430-W2DS419	72	24	30	27	19" EIA	39 RU	304SS	12 ga.	#4 Grain	372.47
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	36D	N4X242436-W2DS419	24	24	36	33	19" EIA	12 RU	304SS	14 ga.	#4 Grain	159.92
Left/Right		N4X302436-W2DS419	30	24	36	33	19" EIA	15 RU	304SS	14 ga.	#4 Grain	178.07
Left/Right		N4X362436-W2DS419	36	24	36	33	19" EIA	18 RU	304SS	14 ga.	#4 Grain	196.99
Left/Right		N4X422436-W2DS419	42	24	36	33	19" EIA	22 RU	304SS	14 ga.	#4 Grain	216.4
Left/Right		N4X482436-W2DS419	48	24	36	33	19" EIA	25 RU	304SS	14 ga.	#4 Grain	241.91
Left/Right		N4X542436-W2DS419	54	24	36	33	19" EIA	29 RU	304SS	14 ga.	#4 Grain	259.35
Left/Right		N4X602436-W2DS419	60	24	36	33	19" EIA	32 RU	304SS	14 ga.	#4 Grain	278.27
Left/Right		N4X662436-W2DS419	66	24	36	33	19" EIA	36 RU	304SS	12 ga.	#4 Grain	392.52
Left/Right		N4X722436-W2DS419	72	24	36	33	19" EIA	39 RU	304SS	12 ga.	#4 Grain	415.33
Left/Right		N4X722436-W2DS419	72	24	36	33	19" EIA	39 RU	304SS	12 ga.	#4 Grain	415.33
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Left/Right	42D	N4X242442-W2DS419	24	24	42	39	19" EIA	12 RU	304SS	14 ga.	#4 Grain	178.79
Left/Right		N4X302442-W2DS419	30	24	42	39	19" EIA	15 RU	304SS	14 ga.	#4 Grain	198.56
Left/Right		N4X362442-W2DS419	36	24	42	39	19" EIA	18 RU	304SS	14 ga.	#4 Grain	219.11
Left/Right		N4X422442-W2DS419	42	24	42	39	19" EIA	22 RU	304SS	14 ga.	#4 Grain	240.14
Left/Right		N4X482442-W2DS419	48	24	42	39	19" EIA	25 RU	304SS	14 ga.	#4 Grain	267.28
Left/Right		N4X542442-W2DS419	54	24	42	39	19" EIA	29 RU	304SS	14 ga.	#4 Grain	286.34
Left/Right		N4X602442-W2DS419	60	24	42	39	19" EIA	32 RU	304SS	14 ga.	#4 Grain	306.89
Left/Right		N4X662442-W2DS419	66	24	42	39	19" EIA	36 RU	304SS	12 ga.	#4 Grain	433.15
Left/Right		N4X722442-W2DS419	72	24	42	39	19" EIA	39 RU	304SS	12 ga.	#4 Grain	458.24
Left/Right		N4X722442-W2DS419	72	24	42	39	19" EIA	39 RU	304SS	12 ga.	#4 Grain	458.24



**FULL ACCESS - NETWORK SERVER - RACKMOUNT CABINET**  
**NEMA 4X STAINLESS STEEL -12RU - AIR-CONDITIONER OPTION**  
**NEMACO PART# N4X242424-W2DS419**