

NEMA 4/4X - UL Listed Enclosure Air Conditioners



AIR CONDITIONING ADVANTAGES:

- Condensate Evaporation Package - Drip-free condensation removal is not an option, it is standard on every air conditioner. No drain tube is needed.
- Programmable Digital Controller - Programmable set point and temperature controls, visible error and/or alarm messaging, and system protection.
- Energy Efficient Operation - Thermal Expansion Valves balance the refrigerant flow to maximize efficiency over a wide temperature and load range.
- 5-Year Warranty - Thermal Edge products are warranted to be free of defects in workmanship, materials and components.



Model	BTU/Hour	Voltage/Phase/Hz	Running Amps	Maximum Ambient Temp	Maximum Integrated Heat (Watts)	H x W x D	Ship Weight
NE010126	1,000	115/1/60	3.44	125°F	NA	22" x 11.8" x 8.5"	65
NE010236	1,000	230/1/60	2.67	125°F	NA	22" x 11.8" x 8.5"	67
CS011D48	1,000	48 VDC	3.7	125°F	NA	17" x 7" x 7"	43
CS011126	1,000	115/1/60	2.7	131°F	350	17" x 7" x 7"	45
NE015126	1,500	115/1/60	3.44	125°F	NA	22" x 11.8" x 8.5"	65
NE015236	1,500	230/1/60	2.67	125°F	NA	22" x 11.8" x 8.5"	67
NE020126	2,000	115/1/60	3.16	128°F	1000	32" x 11.8" x 9.5"	79
NE020236	2,000	230/1/60	1.58	128°F	1000	32" x 11.8" x 9.5"	86
NE020486	2,000	460/1/60	0.79	128°F	1000	38" x 11.8" x 9.5"	113
CS020126	2,000	115/1/60	4.1	131°F	500	20" x 10" x 10"	58
CS020236	2,000	230/1/60	2.0	131°F	500	20" x 10" x 10"	63
NE030126	3,000	115/1/60	4.79	129°F	1000	32" x 11.8" x 9.5"	80
NE030236	3,000	230/1/60	2.39	129°F	1000	32" x 11.8" x 9.5"	86
NE030486	3,000	460/1/60	1.20	129°F	1000	38" x 11.8" x 9.5"	113
NE040D48	4,000	48 VDC	25.3	131°F	NA	35.27" x 11.8" x 9.5"	120
NE040126	4,000	115/1/60	6.53	140°F	1000	32" x 11.8" x 9.5"	80
NE040236	4,000	230/1/60	3.27	140°F	1000	32" x 11.8" x 9.5"	86
NE040486	4,000	460/1/60	1.64	140°F	1000	38" x 11.8" x 9.5"	113
NE050126	5,000	115/1/60	6.87	131°F	1000	36" x 11.8" x 15.1"	111
NE050236	5,000	230/1/60	3.44	131°F	1000	36" x 11.8" x 15.1"	106
NE050486	5,000	460/1/60	1.72	131°F	1000	44.63" x 11.8" x 15.1"	150
NE060126	6,000	115/1/60	7.83	125°F	1000	36" x 11.8" x 15.1"	111
NE060236	6,000	230/1/60	4.8	125°F	1000	36" x 11.8" x 15.1"	112
NE060486	6,000	460/1/60	2.4	125°F	1000	44.63" x 11.8" x 15.1"	156
TM061126	6,000	115/1/60	10.6	131°F	1000	15.6" x 26.3" x 20.2"	163
TM061236	6,000	230/1/60	6.0	131°F	1000	15.6" x 26.3" x 20.2"	163
TM061486	6,000	460/1/60	3.0	131°F	1000	15.6" x 26.3" x 20.2"	206
NE080126	8,000	115/1/60	7.83	125°F	1000	36" x 11.8" x 15.1"	117
NE080236	8,000	230/1/60	4.8	125°F	1000	36" x 11.8" x 15.1"	118
NE080486	8,000	460/1/60	2.4	125°F	1000	44.63" x 11.8" x 15.1"	156
TM081126	8,000	115/1/60	11.6	131°F	1000	15.6" x 26.3" x 20.2"	163
TM081236	8,000	230/1/60	7.0	131°F	1000	15.6" x 26.3" x 20.2"	163
TM081486	8,000	460/1/60	3.5	131°F	1000	15.6" x 26.3" x 20.2"	206
HC101126	10,000	115/1/60	19.4	131°F	1500	48" x 15.9" x 15.1"	182
HC101236	10,000	230/1/60	8.2	131°F	1500	48" x 15.9" x 15.1"	186
HC101486	10,000	460/1/60	4.1	131°F	1500	57.6" x 15.9" x 15.1"	275
HC121126	12,000	115/1/60	19.4	131°F	1500	48" x 15.9" x 15.1"	185
HC121236	12,000	230/1/60	8.2	131°F	1500	48" x 15.9" x 15.1"	183
HC121486	12,000	460/1/60	4.1	131°F	1500	57.6" x 15.9" x 15.1"	280
HC151236	15,000	230/1/60	12.53	131°F	1500	48" x 15.9" x 15.1"	190
HC151486	15,000	460/1/60	6.27	131°F	1500	57.6" x 15.9" x 15.1"	290
HC201236	20,000	230/1/60	18.83	129°F	1500	56.1" x 23" x 15"	225
HC201486	20,000	460/1/60	9.42	129°F	1500	65.7" x 23" x 15"	380

Compact Series (CS)
1,000 - 2,000 BTU/H



Narrow Edge Series (NE)
1,000 - 8,000 BTU/H



High Capacity Series (HC)
10,000 - 20,000 BTU/H



Top Mount Series (TM)
6,000 - 8,000 BTU/H

